

PREMIUM MARINE SANITATION HOSE



101 Series

Trident Premium Sanitation Hose resistant to odor permeation. Simply the BEST solution for marine environments, built with EPDM rubber to ensure the over all performance and resistance to odor permeation that you would expect in a sanitation hose. Excellent bend radius and heat resistance (a big contributor to odor permeation on plastic hoses). 10 Year Warranty.

Tube & Cover: EDPM/SBR Rubber

Color:

Black w/Green Stripe

Reinforcement: Polyester reinforcement

+ spring steel wire helix

	ID		OD		Working Pressure		Weight		Bend Radius	
in.	mm.	in.	mm.	Psi	Bar	Lb./50 ft.	Kg/ 15.24m	in	mm	
1	25.4	1.42	36	80	5.5	32	14.5	1.46	37	
1 1/2	38.1	2	50.8	60	4.1	44	19.9	3	76.2	
1 7/8	47.6	2.38	60.3	50	3.4	64	29	5.75	146	
	1 1 1/2	1 25.4 1 1/2 38.1	1 25.4 1.42 1 1/2 38.1 2	1 25.4 1.42 36 1 1/2 38.1 2 50.8	1 25.4 1.42 36 80 1 1/2 38.1 2 50.8 60	1 25.4 1.42 36 80 5.5 1 1/2 38.1 2 50.8 60 4.1	1. mm. in. mm. Psi Bar ft.	In. mm. In. mm. Psi Bar ft. 15.24m 1 25.4 1.42 36 80 5.5 32 14.5 1 1/2 38.1 2 50.8 60 4.1 44 19.9	In. mm. In. mm. Psi Bar ft. ft. 15.24m in 1 25.4 1.42 36 80 5.5 32 14.5 1.46 1 1/2 38.1 2 50.8 60 4.1 44 19.9 3	

*Burst Pressure is 4 x Working Pressure

Temperature Range:

-20F-220°F (-29°C-104°C)

Coils: 50' (15m) Lengths: 12.5' (3.8m)

TRIDENT RUBBER INC. 585 PLUM RUN ROAD CANONSBURG PA, 15317 1 - 800 - 414 - 2628

WWW.TRIDENTMARINE.COM



Service Ph +64 9 368 0938 · service@generalmarine.co.nz