



**TRIDENT MARINE®**

**BILGE HOSE**



**# 120 / 121 Series**

**Trident** Bilge hose; extremely flexible corrugated polyethylene hose for bilge, intake and discharge. Resists oily bilge and seawater. Cuffed every foot for clamping. Not recommended for below the water line connections.

**Specifications**

**Construction:**

Single layer Corrugated Polyethylene

**Color:**

White #120 Series  
Black #121 Series

**Temperature Range:**

-40°F to 200°F (-40°C to 93°C)

Part Number*	ID		VAC	Weight		Bend Radius	
	in	mm	Vac In./Hg	Lb./50 ft.	Kg/m	In	mm
12x-0580	5/8	15.9	20	3	1.35	0.5	12.7
12x-0340	3/4	19.05	20	4	1.80	0.75	19.05
12x-1180	1-1/8	28.6	20	5	2.25	1.0	25.4
12x-1140	1-1/4	31.7	20	6	2.70	1.2	30.5
12x-1120	1-1/2	38.1	20	7	3.15	1.9	48.3

\* x = 0 for white and 1 for black. (For example 120-0340 is white 3/4" Bilge Hose. 121-0340 is for black).

**Lengths:**

**Bulk Box:** 150' (56 m) to 600' (183 m), **Boxed:** 50'(15.24m) & 100'(30.4m)

**TRIDENT RUBBER INC.**  
585 PLUM RUN ROAD  
CANONSBURG PA, 15317

**1-800-414-2628**

WWW.TRIDENTMARINE.COM



GENERAL  
*Marine*  
SERVICES

156 Beaumont Street · Westhaven · Auckland · New Zealand  
Sales Ph +64 9 309 0048 · sales@generalmarine.co.nz  
Service Ph +64 9 368 0938 · service@generalmarine.co.nz

[www.generalmarine.co.nz](http://www.generalmarine.co.nz)