



TRIDENT MARINE®

TRIDENT BLUE CORA-SIL MARINE EXHAUST & WATER



252V Series

Trident Wet exhaust and water coolant hose offers the BEST performance and flexibility. Silicone naturally handles higher temperatures and will last longer than rubber exhaust Hose. The silicone will also transfer less heat into the engine room. Meets and exceeds Marine Exhaust Standards, SAE J2006, ISO 13363 and is Lloyds Register Certified. 10-year warranty.

Specifications

Tube & Cover:
Wire reinforced
Corrugated silicone

Color: Blue

Reinforcement:
Wire helix and
2-ply polyester

Temperature Range:
350°F (177°C)

Coils:
60'(18.3m)

Lengths:
3'(.91m)
6'(1.83m)
12'(3.65m)

*Burst Pressure is 4 x Working Pressure

| Part Number | ID | | OD | | Working Pressure | | Weight | | Bend Radius | |
|-------------|--------|------|-------|-------|------------------|-----|---------|------|-------------|-------|
| | in. | mm. | in. | mm. | Psi | Bar | Lb./ft. | Kg/m | In | mm |
| 252v0340 | 3/4 | 19.1 | 1.25 | 31.8 | 87.5 | | 8 | | 3 | 76.2 |
| 252v0780 | 7/8 | 22.2 | 1.275 | 32.4 | 78.8 | | 9 | | 3.5 | 88.9 |
| 252v1000 | 1 | 25.4 | 1.5 | 38.1 | 70 | | 9 | | 3.5 | 88.9 |
| 252v1180 | 1-1/8 | 28.6 | 1.625 | 41.3 | 70 | | 8 | | 4 | 101.6 |
| 252v1560 | 1-5/16 | 33.3 | 1.81 | 46 | 57.5 | | 12 | | 5.25 | 133.4 |
| 252v1380 | 1-3/8 | 34.9 | 1.875 | 47.6 | 52.5 | | 8 | | 5.5 | 139.7 |
| 252v1140 | 1-1/4 | 31.8 | 1.75 | 44.5 | 62.5 | | 11 | | 4 | 101.6 |
| 252v1120 | 1-1/2 | 38.1 | 2 | 50.8 | 52.5 | | 9 | | 4.5 | 114.3 |
| 252v1580 | 1-5/8 | 41.3 | 2.125 | 54 | 52.5 | | 13 | | 6 | 152.4 |
| 252v1340 | 1-3/4 | 44.5 | 2.25 | 57.2 | 41.3 | | 9 | | 5 | 127 |
| 252v1780 | 1-7/8 | 47.6 | 2.375 | 60.3 | 41.3 | | 14 | | 6.5 | 165.1 |
| 252v2000 | 2 | 50.8 | 2.6 | 66 | 41.3 | | 15 | | 6.5 | 165.1 |
| 252v2180 | 2-1/8 | 54 | 2.725 | 69.2 | 36.3 | | 17 | | 8.5 | 215.9 |
| 252v2140 | 2-1/4 | 57.2 | 2.85 | 72.4 | 31.3 | | 14 | | 9 | 228.6 |
| 252v2380 | 2-3/8 | 60.3 | 2.975 | 75.6 | 27.5 | | 21 | | 9.5 | 241.3 |
| 252v2120 | 2-1/2 | 63.5 | 3.1 | 78.7 | 27.5 | | 17 | | 10 | 254 |
| 252v2580 | 2-5/8 | 66.7 | 3.225 | 81.9 | 27.5 | | 21 | | 10 | 254 |
| 252v2340 | 2-3/4 | 69.9 | 3.35 | 85.1 | 27.5 | | 20 | | 9 | 228.6 |
| 252v2780 | 2-7/8 | 73 | 3.475 | 88.3 | 27.5 | | 21 | | 10.5 | 266.7 |
| 252v3000 | 3 | 76.2 | 3.6 | 91.4 | 27.5 | | 22 | | 11 | 279.4 |
| 252v3180 | 3-1/8 | 79.4 | 3.725 | 94.6 | 26.3 | | 21 | | 12.5 | 317.5 |
| 252v3140 | 3-1/4 | 82.6 | 3.85 | 97.8 | 25 | | 21 | | 13 | 330.2 |
| 252v3120 | 3-1/2 | 88.9 | 4.1 | 104.1 | 23.8 | | 21 | | 13 | 330.2 |
| 252v4000 | 4 | 102 | 4.7 | 119.4 | 20 | | 24 | | 20 | 508 |
| 252v4120 | 4-1/2 | 114 | 5.2 | 132.1 | 20 | | 32 | | 22.5 | 571.5 |
| 252v5000 | 5 | 127 | 5.7 | 144.8 | 20 | | 40 | | 25 | 635 |
| 252v6000 | 6 | 152 | 6.7 | 170.2 | 20 | | 48 | | 30 | 762 |
| 252v8000 | 8 | 203 | 8.8 | 223.5 | 27.5 | | 56 | | NA | |
| 252v10000 | 10 | 254 | 10.7 | 271.8 | 27.5 | | NA | | NA | |
| 252v12000 | 12 | 305 | 12.7 | 322.6 | 17.5 | | NA | | NA | |
| 252v14000 | 14 | 356 | 14.7 | 373.4 | 17.5 | | NA | | NA | |
| 252v16000 | 16 | 406 | 16.7 | 424.2 | 13.8 | | NA | | NA | |
| 252v18000 | 18 | 457 | 18.7 | 475 | NA | | NA | | NA | |

TRIDENT RUBBER INC.
585 PLUM RUN ROAD
CANONSBURG PA, 15317

1-800-414-2628

WWW.TRIDENTMARINE.COM



GENERAL
Marine
SERVICES

156 Beaumont Street · Westhaven · Auckland · New Zealand

Sales Ph +64 9 309 0048 · sales@generalmarine.co.nz

Service Ph +64 9 368 0938 · service@generalmarine.co.nz

www.generalmarine.co.nz