



TRIDENT MARINE®

A2 FUEL FILL & DIESEL TRANSFER LINE



327 Series

Trident A2 Fuel Fill Hose for gasoline fill hose (including ethanol blends) and diesel (including bio diesel blends). The #327 series exceeds ABYC H-24 & H-33, SAE J1527, ISO 7840, & USCG Type A2; and is NMMA Type Accepted, CE certified and Lloyds Registry Type Approved. This hose is built with the best fuel, fire and age resistant formulation. Provides extraordinary resistance to aging, fire, heat, cold, and the ozone. Also provides excellent bend-ability.

Specifications

Construction:

Tube: NBR

Cover: NBR/EPDM Blend

Reinforcement: High Tenacity Polyester 2 spiral, Spring Steel Helix

Temperature Range: -4°F to 212°F (-20°C to 100°C)

Lengths: 12.5' (3.81 m) **Length**, 12.5' (3.81 m) **Boxed**, 25' (7.62 m) **Boxed**, 50' (15.24 m) **Coil**

Part Number	ID		OD		Wall		Working Pressure		Bend Radius	
	in.	mm.	in.	mm.	in.	mm.	psi	mpa	in.	mm.
327-0340	3/4	19	1.14	29	0.20	5.0	100	0.69	2.5	63.5
327-1000	1	24.5	1.42	36.5	0.215	5.5	80	0.55	3.0	76
327-1140	1-1/4	31.8	1.70	43	0.225	5.7	70	0.48	4.5	114
327-1120	1-1/2	38	2	51	0.25	6.4	60	0.41	5.5	140
327-1580	1-5/8	42	2.13	54	0.25	6.4	50	0.345	6.0	152
327-1780	1-7/8	48	2.38	60.5	0.25	6.4	50	0.345	6.5	165
327-2000	2	50.8	2.48	63.5	0.25	6.4	50	0.345	7.0	178
327-2380	2-3/8	60	2.87	73	0.25	6.4	50	0.345	8.0	203

TRIDENT RUBBER INC.

585 PLUM RUN ROAD
CANONSBURG PA, 15317

1-800-414-2628

WWW.TRIDENTMARINE.COM



GENERAL
Marine
SERVICES

156 Beaumont Street · Westhaven · Auckland · New Zealand

Sales Ph +64 9 309 0048 · sales@generalmarine.co.nz

Service Ph +64 9 368 0938 · service@generalmarine.co.nz

www.generalmarine.co.nz