



TRIDENT MARINE®

A1-15 EPA & CARB COMPLIANT FUEL LINE



365 Series

Trident Barrier Lined A1-15 Fuel Hose for both gasoline (including ethanol blends) and diesel (including bio diesel blends). The #365 series exceeds ABYC H-24 & H-33, SAE J1527, ISO 7840, USCG Type A1-15; CARB Executive Order and EPA Certified low permeation Type A1-15; and is NMMA Type Accepted & CE certified. This hose is built with the best fuel, fire and age resistant formulation and a unique "Barrier Liner" on inside surface of the tube, so fuel is not in direct contact with rubber. Provides extraordinary resistance to fuel permeation, aging, and also to fire, heat, cold, and the ozone. Also provides excellent bend-ability.

Specifications

Construction:

Tube: Nylon Internal Barrier, NBR

Cover: NBR/PVC Blend

Reinforcement: Polyester 2 spiral

Temperature Range: -20°F to 212°F (-28°C to 100°C)

Lengths: 250' (76 m), and 500' (152 m) **Reels**, 100' (30.5 m), 50' (15 m), and 25' (7.6 m) **Boxed**

Part Number	ID		OD		Burst Pressure		Working Pressure		Bend Radius		Weight		Permeation Rate Standard is 15g/m ² /24 hrs (CE10)
	in.	mm.	in.	mm.	psi	mpa	psi	mpa	in.	mm.	lb/100 ft	kg/m	
365-0140	0.250	6.35	0.536	13.6	400	2.76	100	0.69	2.5	63.5	10.8	0.161	< 15
365-0560	0.312	7.92	0.611	15.5	400	2.76	100	0.69	2.5	63.5	13.3	0.198	< 15
365-0380	0.375	9.50	0.681	17.3	400	2.76	100	0.69	2.5	63.5	15.6	0.233	< 15
365-0120	0.500	12.7	0.821	20.9	400	2.76	100	0.69	4.5	114	20.5	0.306	< 15
365-0580	0.625	15.9	1.000	25.4	300	2.07	75	0.52	4.5	114	29.5	0.44	< 15
365-0340	0.750	19.0	1.130	28.7	200	2.07	75	0.52	4.5	114	34.0	0.505	< 15

TRIDENT RUBBER INC.

585 PLUM RUN ROAD
CANONSBURG PA, 15317

1-800-414-2628

WWW.TRIDENTMARINE.COM



GENERAL
Marine
SERVICES

156 Beaumont Street · Westhaven · Auckland · New Zealand

Sales Ph +64 9 309 0048 · sales@generalmarine.co.nz

Service Ph +64 9 368 0938 · service@generalmarine.co.nz

www.generalmarine.co.nz